

REPUBLIC OF BULGARIA

Executive Agency Bulgarian Accreditation Service





ORDER

Nº A 244

Sofia, 14.06.2024

Pursuant to Art. 10, para. 1, items 3 and 4, Art. 28, par. 1 and Art. 30, para. 1 of the Law on National Accreditation of Conformity Assessment Bodies, items 6 and 7 of the BAS QR 2 Accreditation procedure, in connection with an open procedure reg. № 1/3 ЛК/ПА/РО/18.01.2024 assessment report reg. № 1/3 ЛК/6/B/15.03.2024, declaration reg. № 1/3 ЛК/7/P/15.03.2024, report G2 Section reg. № 1/3 ЛК/14/B/09.05.2024, declaration reg. № 1/3 ЛК/10/P/16.04.2024 and statement of the Accreditation Commission reg. № 1/3 ЛК/ПА/РО/16/В/05.06.2024, I hereby

RE-ACCREDIT

METROLAB LTD **INTERLAB LABORATORY COMPLEX**

Management Address: 1359 Sofia, Lyulin, Bl. 408, Ent. A, Floor 2, Apt. 11 Laboratory Address: 1574 Sofia, Slatina, 13 Prof. Tsvetan Lazarov Blvd.

To perform calibrating of:

Nō	of the scope: fixe Measuring instrument	Measured value, unit of measure	Measurement Range	Measurement uncertainty	Calibration method
1	2	3	4	5	6
	Non-automatic scales, Accuracy class I	ccuracy is I	up to 0,5 Kg	1,1.10 ⁻⁵ g	LKI 08-05:2024
	Accuracy class II		up to 1 Kg	8,9.10 ⁻⁴ g	
1.			up to 10 Kg	6,5.10 ⁻² g	
			Kg up to 60 Kg	0,1 g	
	Accuracy class III and IIII		up to 1 Kg	0,01 g	
			up to 10 Kg	0,2 g	
		III dilu IIII	up to 150 Kg	4,2 g	
2.	Wind velocity measuring devices	Velocity	from 0,15 m/s to 2,04 m/s	0,060 m/s	- LKI 10-05:2024
		uring m/s	from 2,02 m/s to 29,83 m/s	from 0,06 m/s to 0,5 m/s	
3.	Thermometers (digital,analog)	Temperature, °C	from minus 50°C to 20°C	from 0,3 °C to 0,05 °C	LKI 14-11:2024

52 A "Dr. G. M. Dimitrov" Blvd. 1797 Sofia Bulgaria phone: +359 2 9766 401; fax: +359 2 9766 415 e-mail: office@nab-bas.bg

ype	of the scope: fixe	Measured value,	Measurement	Measurement	Calibration
Νō	Measuring instrument	unit of measure	Range	uncertainty	method
1	2	3	4	5	6
1			from 20°C to 400 °C	from 0,05 °C to 0,3 °C	
			from 400°C to 700 °C	from 0,3 °C to 2,2 °C	
			from 700°C to 1200 °C	from 2,2 °C to 3,0 °C	
4.	Infrared thermometers	Temperature, °C	from 20°C to 350 °C	from 0,4 °C to 0,8 °C	LKI 14-11:2024
	Thermometers (glass - liquids)	lemperature.	from minus 50°C to 20 °C	from 0,3 °C to 0,05 °C	LKI 13-11:2024
5.			from 20°C to 200°C	from 0,05 °C to 0,19 °C	
			from 200°C to 600°C	from 0,19 °C to 2,2 °C	
	Temperature measuring transducers	Temperature, °C	Resistive - from minus 50 °C to 100°C	from 0,18 °C to 0,25 °C	LKI 15-06:2024
6.			over 100 °C to 400°C	from 0,25 °C to 1,3 °C	
			thermocouple from minus 50°C to 400°C	0,48 °C	
			over 400 °C to 1200°C	from 0,49 °C to 1,6 °C	
7.	Secondary appliances, temperature indicators	appliances, Temperature,	Input for a thermal transformer (RTD) from minus 40 °C to 600 °C	0,1 °C	- LKI 16-06:2024
			Input for thermocouples (TC) from minus 40 °C to 1200 °C	up to 0,4 °C	- LKI 10-00.2024
8.	Instruments for relative humidity measuring	Relative humidity, % rh	from 20 % rh to 85 % rh	from 1,2 % rh to 1,4 % rh	LKI 12-09:2024
9.	pH Meters	Hydrogen index pH	from 2 pH to 12 pH	from 1,8.10 ⁻² pH to 5. 10 ⁻² pH	LKI 09-05:2024
10.	Conductometers	Specific conductivity of electrolytes, µS/cm; mS/cm	from 1,3 µS/cm to 111,3 mS/cm	from 0,02 µS/cm to 1,6 mS/cm	LKI 01-09:2024
11.	Calorimeters	Combustion energy J/g	from 26400 J/g to 26600 J/g	6 J/g	LKI 04-09:2024

Nō	of the scope: fixe Measuring instrument	Measured value, unit of measure	Measurement Range	Measurement uncertainty	Calibration method
1	2	3	4	5	6
12.	Spectrophoto- meters for the ultraviolet and visible areas for the wavelength	Spectral coefficient of $\tau(\lambda)$, % transmission, geometry % relative to air	from 7 % to 93 % at λ from 250 nm to 820 nm	from 0,28 % to 1,4 %	LKI 07-04:2024
		Spectral optical density, D(λ), geometry % relative to air	from 0,02 to 1,12 at λ from 250 nm to 820 nm	from 7.10 ⁻³ to 1,2.10 ⁻²	LKI 07-04:2024 method of calculation
		Wave length λ, nm	from 241 nm to 638 nm	from 0,3 nm to 1 nm	LKI 07-04:2024

References:

1.	LKI 01-09:2024	Methodology for the calibration of conductivity meters using certified comparative materials for the specific electrical conductivity of electrolytes.
2.	LKI 04-09:2024	Calorimeter calibration methodology.
3.	LKI 07-04:2024	Methodology for the calibration of spectrophotometers operating in the ultraviolet and visible area of the optical spectrum.
4.	LKI 08-05:2024	Methodology for the calibration of non-automatic scales.
5.	LKI 09-05:2024	Methodology for the calibration of pH meters.
6.	LKI 10-05:2024	Methodology for the calibration of instruments for measuring air velocity.
7.	LKI 12-09:2024	Methodology for the calibration of devices for measuring relative humidity of the air.
8.	LKI 13-11:2024	Methodology for the calibration of glass-liquid thermometers.
9.	LKI 14-11:2024	Methodology for the calibration of digital, analog and infrared thermometers.
10.	LKI 15-06:2024	Methodology for the calibration of measuring temperature transducers.
11.	LKI 16-06:2024	Methodology for the calibration of secondary temperature measuring instruments.

Notes:

- 1. The calibration of the measuring instruments, referred to in item 2, shall be performed in the laboratory.
- 2. The calibration of the measuring instruments referred to in item 3, item 4, item 5, item 6, item 7, item 8, item 9, item 10 and item 12 shall be performed in the laboratory, or at the customer's site.
- 3. The calibration of the measuring instruments referred to in items 1 and 11 shall be performed on site at the customer's location.

I ORDER

To issue the certificate of accreditation reg. Nº 3 Π K/14.06.2024 valid until 14.06.2028 and this order enclosed as an integral part of it.

The certificate of accreditation with the enclosure should be obtained from the Manager/Representative of Metrolab Ltd, the head of Interlab Laboratory Complex at Metrolab Ltd, or other authorized person in the office of EA BAS.

Upon receipt of the certificate issued and enclosure, the accredited person is obliged to return to EA BAS the originals of certificate of accreditation reg. N° 3 JK/13.10.2023 and its enclosure, EA BAS order reg. N° A 442/13.10.2023.

This order shall be notified to the legal entity, within 3 (three) days from its issuance.

Eng. Irena Borislavova

Executive Director of EA BAS